

RADIAL FLOW SERIES

STANDARD PRODUCT LIST V3 PS Series														
V3 Motor Max OD 73 mm 1 Ph 220 Volts, 50 Hz							Pump SS Jacket with Noryl Diffuser & Impellers							
V3 PS2 Series							DISCHARGE IN LPM							
Sr	Model	H.P	Stage	K.W.	D.O.	% Effi.	25	30	35	40	45	50	55	60
1	F10 PS2 0.50	0.50	10	0.37	1.25"	21	40	37	35	30	25	20	15	10
2	F15 PS2 0.75	0.75	15	0.55	1.25"	22	60	56	52	45	37	30	22	15
3	F20 PS2 1.00	1.00	20	0.75	1.25"	24	80	75	70	60	50	40	30	20
4	F30 PS2 1.50	1.50	30	1.1	1.25"	26	120	113	105	90	75	60	45	30
V3 PS3 Series							DISCHARGE IN LPM							
Sr	Model	H.P	Stage	K.W.	D.O.	% Effi.	30	45	55	60	65	70	75	80
1	F05 PS3 0.50	0.50	5	0.37	1.25"	23	20	18	17	16	15	14	12	10
2	F08 PS3 0.75	0.75	8	0.55	1.25"	24	32	30	28	26	24	22	20	16
3	F10 PS3 1.00	1.00	10	0.75	1.25"	26	40	37	35	32	30	27	25	20
4	F15 PS3 1.50	1.50	15	1.1	1.25"	27	60	56	52	49	45	41	37	30
V3 PS7 Series							DISCHARGE IN LPM							
Sr	Model	H.P	Stage	K.W.	D.O.	% Effi.	20	30	40	50	60	70	80	90
1	F06 PS7 0.50	0.50	6	0.37	1.25"	22	25	24	21	19	18	16	15	12
2	F08 PS7 0.75	0.75	8	0.55	1.25"	23	34	32	28	26	24	22	20	16
3	F12 PS7 1.00	1.00	12	0.75	1.25"	25	51	48	42	39	36	33	30	24
4	F18 PS7 1.50	1.50	18	1.1	1.25"	27	77	72	63	59	54	49	45	36

STANDARD PRODUCT LIST V3 PS Series														
V3 Motor Max OD 73 mm 1 Ph 220 Volts, 50 Hz							Pump SS Jacket with Noryl Diffuser & Impellers							
V3 PS3 Series							DISCHARGE IN LPM							
Sr	Model	H.P	Stage	K.W.	D.O.	% Effi.	30	45	55	60	65	70	75	80
1	F10 PS3 1.00 Ø1-V3-(W.C.P)	1.00	10	0.75	1.25"	26	40	37	35	32	30	27	25	20
2	F15 PS3 1.50 Ø1-V3-(W.C.P)	1.50	15	1.1	1.25"	27	60	56	52	49	45	41	37	30

Sr	Model	H.P	Stage	K.W.	D.O.	% Effi.	20	30	40	50	60	70	80	90
1	F12 PS7 1.00 Ø1-V3-(W.C.P)	1.00	12	0.75	1.25"	25	51	48	42	39	36	33	30	24
2	F18 PS7 1.50 Ø1-V3-(W.C.P)	1.50	18	1.1	1.25"	27	77	72	63	59	54	49	45	36