

V4 Mix Flow CI Bowl (SINGLE PHASE)

V4 Mix Flow CI Bowl (SINGLE PHASE)														
V4 Motor Max OD 96 mm 1 Ph 220 Volts							Pump S.S. Impeller & C.I Bowl							
PSMC18 Copper Rotor							DISCHARGE IN LPM							
Sr	Model	H.P	Stage	K.W.	D.O.	% Effi.	70	150	200	230	300	380	450	520
1	A06 PSMC18 2.00 1Ø	2	6	1.5	65	31	33	30	27	24	21	18	15	12
2	A08 PSMC18 3.00 1Ø	3	5	2.2	65	34	44	40	36	32	28	24	20	16
3	A12 PSMC18 5.00 1Ø	5	12	3.7	65	36	66	60	54	48	42	36	30	24
4	A14 PSMC18 5.00 1Ø	5	14	3.7	65	36	77	70	63	56	49	42	35	28

V4 Mix Flow CI Bowl (THREE PHASE)

V4 Mix Flow CI Bowl (THREE PHASE)														
V4 Motor Max OD 96 mm 3 Ph 415 Volts							Pump S.S. Impeller & C.I Bowl							
PSMC18 Copper Rotor														
Sr	Model	H.P	Stage	K.W.	D.O.	% Effi.	70	150	200	230	300	380	450	520
5	A06 PSMC18 2.00 3Ø	2	6	1.5	65	38	33	30	27	24	21	18	15	12
6	A08 PSMC18 3.00 3Ø	3	5	2.2	65	42	44	40	36	32	28	24	20	16
7	A12 PSMC18 5.00 3Ø	5	12	3.7	65	44	66	60	54	48	42	36	30	24
8	A14 PSMC18 5.00 3Ø	5	14	3.7	65	44	77	70	63	56	49	42	35	28